

CONSTITUTION

INDIANAPOLIS RADIO CONTROL MODELERS CLUB

ARTICLE I -- Name

1.0 The name of this organization shall be the Indianapolis Radio Control Modelers Club

ARTICLE II -- Objectives

1.0 The objectives of this organization shall be to promote modeling and its associated educational and recreational activities.

ARTICLE III -- Policies

1.0 This organization shall be a nonprofit incorporated association.

2.0 Neither the name nor the activities of this club shall be associated with any outside organization or partisan activity not in the best interest of radio control modeling.

3.0 Activities of this organization shall be directed exclusively to plans and projects promoting the best interests of the club and its members.

ARTICLE IV -- Membership and Dues

1.0 Membership in this organization is open to all individuals interested in radio control modeling, subject to the conditions listed in the subsequent paragraphs of the Articles.

2.0 Membership is classed as OPEN, JUNIOR, FAMILY and DEPENDENT. OPEN and JUNIOR memberships are defined by the current regulations of the Academy of Model Aeronautics (AMA). FAMILY membership covers the OPEN member as well as JUNIOR member dependents and the spouse of an OPEN member. A DEPENDENT member shall be defined as a dependent of an OPEN member and shall not have reached their 16th birthday before July 1st of the year of membership. DEPENDENT members receive no club newsletter.

3.0 Membership in the club shall include only individuals belonging to the Academy of Model Aeronautics.

4.0 Club membership ends each year on December 31st regardless of the date a membership application is received.

5.0 Late year membership is as follows: Those who join from September 1st through December 31st pay full next year's rate and receive membership for the following year plus whatever days membership remain in the year of application.

5.1 The determination of the amount of club dues for all membership categories for the succeeding year shall be by the majority vote of the membership upon the recommendation of the Executive Board, at a time no later than the September meeting of the current year.

5.2 Full club dues shall be paid annually by OPEN and FAMILY members, subject to the provisions in paragraph 5.3.

5.3 Those renewing membership after the end of the February meeting shall pay a penalty. The amount of the penalty for the succeeding year shall be determined by the majority vote of the membership upon the recommendation of the Executive Board, at a time no later than the September meeting of the current year.

5.4 Club dues for JUNIOR members shall be one-half the OPEN member fee.

5.5 Club dues for DEPENDENT members shall be waived.

ARTICLE V -- Officers and Elections

1.0 Any member in good standing for a period of at least six months is eligible to hold office.

2.0 Officers shall consist of a President, Vice President, Secretary and Treasurer. Officers shall serve a period of one year or until their successors are elected and installed.

3.0 The President shall appoint a nomination committee composed of three members. They shall nominate a minimum of two members in good standing for each office at the November meeting each year. Nominations may also be made from the floor at this meeting. All nominees shall have consented to run for office prior to nomination.

4.0 Election shall be by secret ballot at the December meeting each year. Election of an officer shall be based on a majority of all votes.

5.0 Newly elected officers shall assume office January 1, each year.

ARTICLE VI -- The Executive Board

1.0 The elected officers of the club are the Executive Board.

2.0 This board shall formulate the general policies of the organization and shall act on all necessary matters of the business in the interim period between meetings of the organization.

3.0 The Executive Board shall fill, by appointment, any vacancy of office of the organization until the next regular election.

4.0 This Board shall meet at least quarterly during the year or whenever called by the President.

5.0 Three members of the Executive Board shall constitute a quorum for the transaction of business.

ARTICLE VII -- Duties of Officers

1.0 The **President** shall preside at all meetings, shall appoint each Special Committee as are necessary for the proper conduct of business of the organization, and shall serve as ex-officio of each.

2.0 The **Vice President** shall preside in the absence of the President and shall assume the duties of the office of President in such an event and shall be a member of the committees.

3.0 The **Secretary** shall keep the minutes of all meetings, shall notify all Chairmen of their appointments and shall conduct such correspondence as may be delegated to the office.

4.0 The **Treasurer** shall be custodian of all funds, and shall maintain such funds and make such payments as are authorized by the organization, and shall keep accurate records of receipts, and expenditures, and shall submit a monthly report to the membership showing all transactions by the club and the current state of the budget in light of these transactions. This monthly reporting shall include a final yearly summary at the end of the fiscal year. Fiscal year to run from October 1st to September 31st of each calendar year.

5.0 A **Special Committee** for budgeting shall be appointed yearly in accordance with Article VII section 1.0. This committee shall be appointed no later than one month prior to the end of the fiscal year. The committee should be a minimum of 2 members and shall be composed such that at least 50% of its members are not current officers. Said committee to create a budget for the club to be agreed upon between the committee members and subsequently approved by the executive board by the first meeting of the new fiscal year. The budget is to be presented to the membership at the first meeting of the fiscal year. Budget thus created is not binding but should reflect the needs and expectations of the club and is provided for use by the Treasurer in his aforementioned monthly reports.

ARTICLE VIII -- Meeting of the Organization

1.0 The Organization shall hold regular meetings on the first Monday of each month and at other times as called by the Executive Board.

2.0 Thirty percent of the members in good standing shall constitute a quorum necessary for the conduct of business.

3.0 Robert's Rule of Order, Revised, when not in conflict with this Constitution, shall govern the proceedings of the Organization.

ARTICLE IX -- By Laws

1.0 The Executive Board and three club members appointed by the President shall serve as a Standing Committee to formulate and propose By Laws governing club activities. Proposals shall be enacted by the affirmative vote of two-thirds of the members present at a regular monthly club meeting.

ARTICLE X -- Amendments

1.0 This Constitution may be amended by a two-thirds vote of the membership at any regular meeting of the organization, provided notice of intent to amend has been given at a previous meeting.

INDIANAPOLIS RADIO CONTROL MODELERS CLUB

BYLAWS

Revised February 2010 AIRPORT REGULATIONS

Everyone has joined this club to have fun flying radio control aircraft. Each member has the right to maximum enjoyment of their hobby, and each member has the responsibility of helping others pursue the same objective. These airport regulations, based on common sense and safety, have therefore been enacted in order that each member may obtain maximum benefit from the flying site.

A. GROUND CONTROL

1. Automobiles must be parked in assigned areas to avoid congestion and blocking runways.
2. Engine run-in is restricted to the far north or south end of the field.
3. Spectators are welcome at the flying site and should be shown the courtesy their interest warrants.

The following rules apply:

- (a) Spectators should remain in assigned areas unless invited into pit area by a member.
- (b) All children must be accompanied by, and under direct supervision, of an adult.

B. FIELD RULES

These are the rules for safe operating practices at the Indianapolis Radio Control Modelers Field. These rules are to be followed every time you are at the field, whether it be alone or with other persons present!

1. No transmitter is to be turned on without first clearing your frequency and placing your club membership card in the proper slot in the frequency board. It is also good to find out what other fliers' frequencies are and to let them know what yours is. **NO CARD - NO FLY.** Those with radios using Spread Spectrum or other similar technologies that do not require a "channel" are still required to post their club cards or AMA membership card in the frequency board using either the slots provided (if any) or using the amateur radio slots provided if no other facility has been provided.

- (a) All transmitters and receivers **must** meet all current AMA and FCC regulations. (Reference the **2010 AMA Membership Manual** starting on page 9)

2. We reserve the right to sound test any aircraft that we feel jeopardizes the use of our field. If in the opinion of 3 (three) club members to a possible sound issue, the pilot could be ask to land and will not fly said aircraft until at such time it can be sound tested by the following guideline(s):

The aircraft is to be positioned on the ground and the engine run at full throttle. Sound Meter set to the "A" scale, slow response, windscreen on. The meter will be positioned twenty-five feet from the model, downwind, abeam the prop arc, set at twenty four inches in height. The meter will point directly at the prop arc. The maximum sound levels (measured per the above listed measurement standard) are 96 decibels measured on grass (98 on hard surface).

3. Any run-in of engines must be done in the designated area. The engines being run-in must meet the requirements of paragraph B.2. above.

4. Do not let your airplane get any farther than an arm's reach from you while taxiing to and from the runway. Note: Helicopters typically cannot "taxi" in the classical sense and should therefore be carried to and from the runway. A "hover taxi" is considered flying and as such should not occur behind the pilot stations at any time.

5. First pilot to the runway designates the active runway.

a. This person shall determine the active runway by the following: The runway AGAINST the prevailing wind or closest to it.

b. Pilots that encounter an emergency such as radio interference, dead stick, etc., and wish to land, must state their situation to obtain priority for landing.

c. Direction of active runway may be changed by a unanimous agreement of all fliers currently in the air during a change in wind direction.

6. All pilots with planes in the air will stand in one of the flight stations. A maximum of 4 planes are allowed in the air at one time.

7. All flight is to be restricted to an area South of the northern border of the club property and East of the flight line. There will be **NO** low passes toward the pits. Be aware of low flying full-scale aircraft. If a full scale aircraft approaches the field all model aircraft must immediately drop below the height of the surrounding trees.

8. The field is to be used for radio controlled models only. All model types are required to follow all field rules, both stated and implied.

9. No one flies without AMA membership! **NO EXCEPTIONS!** You must have your club membership card in the frequency board before turning on your transmitter.

10. Members may invite guests to fly at the club field. Each guest may fly no more than 3 days per year. Any other circumstances must have the consent of the Standing Committee. The member is fully responsible for the actions their guests.

Violations of rules by guests will be considered as violations by the member. Guest will use their AMA card in the frequency board to identify their frequency.

11. Visitors and spectators are not allowed in the pit area without escort of a club member. All pets (dogs, cats, etc.) brought to the field must be kept in the vehicle or on a leash and restrained by the owner when outside the vehicle.

12. Pilots must not consume alcoholic beverages prior to, nor during, participation in any model operations.

13. Any person that flies solo must have an instructor present or have passed the LEVEL 2 requirement of the Achievement Program.

14. Gliders using a "High start" may only be used when powered aircraft are not present.

15. All aircraft must be pitted within 10 feet of the safety fence (on the runway side of the fence) and when starting engines

16. All aircraft shall be flown in accordance with AMA safety requirements including the requirement for AMA number or name and address attached to the aircraft.

17. A range check shall be performed on all aircraft prior to the first flight each day.

18. All new/repared aircraft shall be preflight inspected to the criteria of the Preflight Checklist (appendix a) prior to flight.

19. The president shall appoint a safety officer that is responsible for monitoring the member's conformance to the airport regulations however, all members are responsible to insure members and guests follow the rules.

20. A collection overflow device shall be used when fueling aircraft to minimize spillage of fuel on the ground.

21. For safety reasons No flying is allowed while the runway and pits are being mowed.

22. No trash of any kind will be left at the field. If you brought it with you – take it home.

23. Allowed flying times are as follows:

For electric powered or glider aircraft – 8:00AM to dusk every day.

For all other aircraft – 9:00AM to dusk Monday through Saturday,
12:00pm (noon) to dusk on Sunday.

24. Last club member leaving the field for the day must make sure the flag has been lowered and put away and the buildings and equipment lockers are secure, and lock the gate.

Any type of flying that endangers people or property at the field will not be tolerated. It is the responsibility of every member to follow and enforce these rules. Don't be afraid to remind any violator of their obligation to follow the above rules.

C. ACHIEVEMENT PROGRAM

The initial intention of the achievement program is to provide the novice with adequate instruction to enable him or her to build and fly a radio controlled aircraft in a safe and controlled manner.

NOTES:

1. Flyers up grading to Levels 3 or 4 must pass that grade level as judged by three flyers that are at least Level 2 and have a working knowledge of the requirements. At least two of the three judges must agree that each maneuver is performed satisfactorily for the Level to be passed. Certification flights may take place on different days however; the entire sequence must be flown and witnessed by each judge during one flight.
2. An instructor is not financially responsible for a student's aircraft in case of damage or a crash.
3. Pilots advancing to any Level must exhibit self control during any emergency or accident.
4. Flyers upgrading to Level 2 must pass that grade level as judged by an instructor and another observer of Level 2 or above. Instructor and Observer should grade each of the following activities, using an A, B, C, D or F for each activity. Student must get a C or better to pass. Any grade of D or F should be explained to the student and the student should be allowed to retest as soon as they wish. The idea of grading is to use this as a further learning opportunity for the student, so that they can understand what they need to continue to work on even if they achieve the new level.

LEVEL 2 PILOT To attain the pilot rating, a novice must be able to:

1. **Know and exhibit proper field behavior concerning flying boundaries and courtesy, pit conduct and use of the frequency board.** The student should check the frequency board and insure his/her card is in the correct slot before activating their radio. They should also observe proper communication and observe no fly boundaries during the entire flight.
2. **Perform a preflight check of aircraft and radio equipment.** This should include, but is not limited to a check of battery condition, proper control surface movement and a standard range check.
3. **Prepare aircraft for flight and start/tune engine.** The student should fuel and start aircraft without assistance while maintaining safe operating procedure.
4. **Perform 2 unassisted takeoffs.** One in each direction. The student should take off and land (see item 6) in a direction approximately parallel to the center line of the runway in each direction. The student should exhibit reasonable control during the taxi and takeoff roll such that safety is maintained.
5. **Exhibit controlled flight by a series of left and right turns.** The student should fly a standard 4 cornered race track pattern or something similar to prove their control over the aircraft.

6. **Perform 2 controlled landings.** The student should land as described in item 4. After landing the student should taxi back to the pilot station area or the pits as they wish. Killing the engine on landing via a prop strike on the ground is NOT necessarily grounds for a failing grade but should be discouraged as this is typically a sign that the student needs more practice.

7. **Exhibit controlled flight during a simulated dead stick landing approach.** (Instructor has novice bring engine to idle and Novice Pilot must make a safe approach to runway – power can be applied before a landing is made) This landing may vary somewhat from a perfect parallel approach from the runway center line but should NOT be made directly in the direction of the spectators, parking lot or pits. Student pilots should recognize that safety is the paramount issue, not recovery of their airplane. Landing in the long grass or field areas is acceptable.

Note: It is recommended that all new Level 2 pilots use an observer during the first 30 days following certification.

LEVEL 3 EXPERIENCED To achieve Level 3, a pilot must:

1. Have knowledge of all transmitter stick modes. The pilot should be able to explain the control layout of a 4 channel radio using modes I and II, including which control surfaces are affected by which stick movements.

2. Perform the following maneuvers during one flight/consecutive flights:

a. **Takeoff with turnout both left and right traffic patterns.** This should include taxiing from the pits to the runway, exhibiting safety and control of the aircraft at all times.

b. **Sustained inverted flight** including left and right turns for the length of the runway. This would best be exhibited by either a complete “lap” around the pattern or horizontal figure 8 around the field while inverted.

c. **Three consecutive inside loops.** Inside loops are loops where the canopy or top of the aircraft faces the inside of the circle drawn. They may be entered from either upright or inverted at the pilot’s option. Loops should exhibit control not simply “full up”. The loops should have a constant radius, i.e. look round, and should not have flat spots. Ideally the entry and exit point to the loops should be constant in both distances from the pilot as well as altitude above the ground.

d. **Three consecutive outside loops.** Outside loops are loops where the wheels or bottom of the aircraft faces the inside of the circle drawn. They can be entered either upright or inverted at the pilot’s option and should be judged similarly to the inside loops above.

e. **Three consecutive rolls,** left or right. The pilot will perform 3 consecutive aileron rolls in whichever direction the pilot decides. The rolls should be one constant maneuver, i.e. no

pauses between rolls. The pilot should enter the maneuver from a straight and level heading (i.e. no pitching up into the maneuver). The pilot should enter and exit the maneuver at the same altitude and heading on which he entered.

f. **Landing patterns both left and right** with a touch and go on the first. The pilot should fly a complete, rectangular landing pattern, complete with four distinct turns and lines. On the first (either downwind or upwind as the pilot wishes) the aircraft should touch at least its main landing gear on the ground and then throttle up and continue the flight, i.e. “touch and go”. The second

approach should be done in the opposite direction and should result in a safe landing and taxi off of the runway.

g. **A Three turn spin**, at a safe altitude, left or right. The pilot should enter from a straight and level attitude and should stall the aircraft on entry. The aircraft should be continuing on heading and without altitude change up the entry to the spin. Ideally the nose should drop as the wing drops to one side, indicating proper spin entry. The pilot should complete the three spins with the nose of the airplane straight down or nearly so and should stop rotation and continue to fly straight down for a short distance to show control. The pilot should then pull out back to level flight in the same direction as the plane was flying upon entry. A spin has not been executed if the aircraft appears to fly into a nose down attitude or if the plane makes a significant amount of wing rotation before the nose drops. This is considered a forced entry and is not acceptable.

LEVEL 4 EXPERT To Achieve Level 4, a Level 3 pilot must:

1. **Exhibit self control during any emergency or minor accident to lesser experienced fliers.** This is not really a measurable parameter but it is important that a pilot at this level be willing and able to help less experienced pilots in the case of any event involving safety of members and spectators. Pilots at this level are expected to be more vigilant in this regard and are encouraged to keep safety first, even if that means landing in the corn rather than trying to guide a partially out of control model back onto the field where it might endanger others; or perhaps NOT flying if there is any doubt as to the flight worthiness of a model aircraft.

2. **Perform the following maneuvers during one flight/consecutive flights:**

a. **Double Immelman** The pilot should enter the maneuver from straight and level flight and should draw a line parallel to the flight line and at a constant altitude. The aircraft should pull a half loop (which should be one continuous radius without flat spots and with wings remaining level). Immediately upon reaching level inverted flight the pilot should execute a half roll to upright. The pilot should then draw another line as before but now flying in the opposite direction. The pilot should then push an outside half loop (again constant radius and wings level) immediately followed by a roll to upright. The pilot should then fly the final line of the maneuver in the same direction as the original entry line, once again straight, level and parallel to the flight line. The two half loops should be of equal radii with the result that the aircraft enters and exits the maneuver at the same altitude.

b. **Humpty Bump** To perform a Humpty Bump the pilot starts straight and level parallel to the flight line and then pulls up into a vertical up line. The pull up should be one continuous radius without flat spots during which the wings remain level. After establishing the up line, the pilot then pulls a half loop into a vertical down line. This half loop should again be one

continuous pull with the aircraft ending in a direct downward path. The aircraft then should establish a down line before pulling once again back to straight and level. Finally a straight and level exit line should be established. This final $\frac{1}{4}$ loop is judged similarly to all of the previous partial loops. The initial (entry) $\frac{1}{4}$ loop and the final exit $\frac{1}{4}$ loop should be of equal radius however the top $\frac{1}{2}$ loop does not have to be of equal size, nor does the entry and exit altitude have to be similar.

c. **Avalanche** An Avalanche is simply a loop with a full positive snap roll at the top of the loop. In order to do this correctly the pilot should perform the following. The pilot should enter

the maneuver from straight and level flight. The pilot will pull up into a half loop then complete a positive snap roll centered on the top of the loop and then complete the other half of the loop. The complete loop should appear circular to the observers and should be completed at the same point where it began both in respect to altitude and distance from the flight line.

d. **Inverted Spin** - three turns The pilot should enter from a straight and level inverted flight and should stall the aircraft on entry. The aircraft should be continuing on heading and without altitude change up to the entry to the spin. Ideally the nose should drop as the wing drops on one side, indicating proper spin entry. The pilot should complete the three spins with the nose of the airplane straight down or nearly so and should stop rotation and continue to fly straight down for a short distance to show control. The pilot should then push back to level inverted flight in the same direction as the plane was flying upon entry. A spin has not been executed if the aircraft appears to fly into a nose down attitude or if the plane makes a significant amount of wing rotation before the nose drops. This is considered a forced entry and is not acceptable.

e. **Slow Roll** The aircraft should enter from straight and level on a path parallel to the runway then execute a 360 degree roll. During the entire roll the aircraft should maintain altitude and heading. As in all maneuvers the roll should be smooth and continuous without noticeable pauses or changes in speed. The roll should end back at straight and level and on the same heading as the maneuver began and should be performed at a point centered in front of the pilot. The rate of roll should be approximately one roll per 3 seconds or slower.

f. **Vertical Up line with 2 point roll** The pilot should begin straight and level and pull into a vertical up line in one smooth continuous pull. After establishing an up line the aircraft should perform a two point roll by rolling 180 degrees then pausing before performing another 180 degree rolls in the same direction. The rolls should be smooth and continuous with a constant roll rate throughout each and similarly between the two $\frac{1}{2}$ rolls. After finishing the rolls the aircraft should continue the up line far enough that the roll maneuver is centered on the up line. Once reaching the top of the maneuver the aircraft should push to level flight on the same heading as the maneuver started.

g. **Four point roll** The pilot should begin as always from straight and level flight and should finish with wings level and heading as well as altitude unchanged. The aircraft should roll at a constant rate between each of the roll "points" and should pause only briefly (long enough for the observer to note the pause) at each point. There should be 90 degrees of rotation between each point. Each 90 degrees of roll should take the same elapsed time to complete. The roll can be in either direction of rotation at the pilot's discretion.

h. **Knife Edge pass** The pilot should enter from straight and level then roll 90 degrees to an attitude where the wings of the aircraft are perpendicular (90 degrees) to the horizon. The

aircraft should hold this attitude and its altitude for approximately the length of the runway. The aircraft should then roll back to level flight. As in all maneuvers the rolls into and out of the knife edge pass should be smooth and continuous. The aircraft should (ideally) trace a straight line parallel to the runway and maintain altitude and heading throughout the maneuver.

i. **Reverse Cuban eight** The pilot should once again begin this maneuver from a straight and level path parallel to the runway then pull into a 45° up line. Midway up this line the aircraft should roll to inverted. At the top the aircraft will perform a $\frac{3}{4}$ inside loop ending in a 45 degree

up line in a direction opposite the initial heading on entry. Midway up this line the pilot should once again roll to inverted. At the top of this line, the aircraft will pull a 5/8ths loop to a wings level exit on the same heading which the maneuver started. All of the loop elements (entry 1/8th loop, 3/4 loop and 5/8th loop to exit) should be a constant radius and the wings should remain level. The result should be that the aircraft enters and exits at the same altitude.

GENERAL:

1. Only members with a Level 2 or higher rating will be allowed to fly solo.
2. A Novice must have an instructor to fly.
3. It will be the airplane owners' responsibility to assure that the aircraft is in good flying condition.
4. The Achievement Program is mandatory through Level 2.